

ZR190KCE-TFD

HFC, R-407C, 50Hz, 3- Phase, 380/420 V

Air Conditioning



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

<u>Evap(°F)/Cond(°F)</u>	<u>45 / 130</u>	<u>35 / 120</u>
<u>RG(°F)/SubCool(°F)</u>	<u>65 / 15</u>	<u>55 / 15</u>
Capacity (Btu/hr)	150000	130000
Power (Watts):	13650	12000
Current (Amps):	26.45	24.50
EER (Btu/Wh):	11.00	10.80
Mass Flow (lbs/hr):	2180	1815
Sound Power (dBA):	82 Avg	87 Max
Vibration (mils(peak-)	3.0 Avg	4.5 Max
Record Date:	2008-01-08	

Mechanical

Number of Cylinders:	0	Displ(in ³ /Rev):	15.20
Bore Size(in):	0.00	Displ(ft ³ /hr):	1530.75
Stroke(in):	0.00		
Overall Length (in):	10.38	Mounting Length (in):	7.50
Overall Width (in):	11.23	Mounting Width (in):	7.50
Overall Height (in):	21.72	Mounting Height (in):	23.03 *
Suction Size (in):	1 3/8 Stub		
Discharge Size (in):	7/8 Stub		
Oil Recharge (oz):	106		
Initial Oil Charge (oz):	110		
Net Weight (lbs):	146		
Internal Free Volume (in ³):	856.0		
Horse Power:			
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	174.0	MCC (Amps):	42.0	UL File No:	SA-2337
LRA-Half Winding:		RPM:		UL File Date:	27-Sep-1996
LRA Low*:	157.0	Max Operating Current:	34.0		
RLA(=MCC/1.4;use for contactor selection):			30		
RLA(=MCC/1.56;use for breaker & wire size)			26.9		
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Alternate Applications

<u>Refrigerant</u>	<u>Freq (Hz)</u>	<u>Phase</u>	<u>Voltage</u>	<u>Application</u>
R-134a HFC	60	3	460	Air Conditioning
R-407C HFC	60	3	460	Air Conditioning
R-134a HFC	50	3	380/420	Air Conditioning