

DANFOSS H SERİSİ SCROLL KOMPRESÖRLER

R404A / R507 - R407C - R134A

MODEL	KOD NO	Btu. 50 Hz.	DİSP. CC	NOMİNAL GÜÇ	VOLTAJ	EMME BASMA		ÇALIŞMA REJİMİ	YAĞ MİKTARI
HRP034 T5LP6	120U2019	28.333	46,21	2,8 Hp	220 V	3/4"	1/2"	+15°C / -20 °C (MBP)	1,06 LT
HRP034 T4LP6	120U2024	28.333	46,21	2,8 Hp	380 V / 400V 50HZ 460V 60HZ	3/4"	1/2"		1,06 LT
HRP040 T4LP6	120U1016	33.333	54,4	3,3 Hp		3/4"	1/2"		1,06 LT
HRP048 T4LP6	120U1656	38.400	64,4	4 Hp		7/8"	1/2"		1,57 LT
HRP060 T4LP6	120U1726	48.000	80,95	5 Hp		7/8"	1/2"		1,57 LT
HLP072 T4LC6	120U1756	57.600	98,65	6 Hp		7/8"	1/2"		1,57 LT
HLP081 T4LC6	120U1781	64.800	110,94	6,5 Hp		7/8"	3/4"		1,57 LT
HCP094 T4LC6	120U0601	75.200	126,02	8 Hp		11/8"	7/8"		2,66 LT
HCP109 T4LC6	120U0376	87.200	148,79	9 Hp		11/8"	7/8"		2,66 LT
HCP120 T4LC6	120U0401	96.000	162,4	10 Hp		11/8"	7/8"		2,66 LT

DANFOSS H SERİSİ TANDEM KOMPRESÖRLER

HRP048 T4LC8	120U1661	38.400	64,4	4 Hp	380 V / 400V 50HZ 460V 60HZ	7/8"	1/2"	+15°C / -20 °C (MBP)	1,57 LT
HRP060 T4LC8	120U1731	48.000	80,95	5 Hp		7/8"	1/2"		1,57 LT
HLP072 T4LC8	120U2072	57.600	98,65	6 Hp		7/8"	1/2"		1,57 LT
HLP081 T4LC8	120U1786	64.800	110,94	6,5 Hp		7/8"	3/4"		1,57 LT
HCP094 T4LC8	120U0611	75.200	126,02	8 Hp		11/8"	7/8"		2,66 LT
HCP109 T4LC8	120U0386	87.200	148,79	9 Hp		11/8"	7/8"		2,66 LT
HCP120 T4LC8	120U0411	96.000	162,4	10 Hp		11/8"	7/8"		2,66 LT

* Kompresörler kaynak bağlantılıdır.

Model	Voltaj	Evaporasyon								
		Kondenzasyon								
		-25 °C	-20 °C	-15 °C	-10 °C	-5 °C	0 °C	+5 °C	+10 °C	
HRP034 T5LP6		40 °C	2.002	2.695	3.496	4.430	5.523	6.802	8.292	10.020
		50 °C	-	-	2.987	3.818	4.795	5.944	7.290	8.859
HRP034 T4LP6		40 °C	2.129	2.759	3.518	4.424	5.496	6.749	8.203	9.874
		50 °C	-	-	2.976	3.779	4.727	5.838	7.130	8.620
HRP040 T4LP6		40 °C	2.445	3.169	4.041	5.082	6.313	7.753	9.423	11.340
		50 °C	-	-	3.416	4.338	5.426	6.702	8.185	9.896
HRP048 T4LP6		40 °C	2.971	3.846	4.902	6.165	7.658	9.406	11.430	13.760
		50 °C	-	-	4.160	5.279	6.603	8.155	9.961	12.040
HRP060 T4LP6		40 °C	3.726	4.801	6.110	7.681	9.544	11.730	14.260	17.180
		50 °C	-	-	55.232	6.612	8.530	10.180	12.430	15.030
HLP072 T4LC6		40 °C	4.746	6.111	7.753	9.719	12.060	14.810	18.030	21.770
		50 °C	-	-	6.529	8.148	10.100	12.420	15.170	18.390
HLP081 T4LC6		40 °C	5.051	6.454	8.190	10.290	12.790	15.710	19.100	22.970
		50 °C	-	-	7.237	9.130	11.400	14.080	17.210	20.810
HCP094 T4LP6		40 °C	5.720	7.374	9.387	11.800	14.660	18.010	21.890	26.340
		50 °C	-	-	8.068	10.220	12.780	15.780	19.280	23.300
HCP109 T4LC6		40 °C	7.254	8.949	11.290	14.240	17.750	21.780	26.280	31.210
		50 °C	-	-	9.893	12.300	15.360	19.030	23.270	28.030
HCP120 T4LC6		40 °C	8.045	9.902	12.450	15.640	19.460	23.860	28.820	34.300
		50 °C	-	-	10.870	13.410	16.670	20.620	25.250	30.500