

DANFOSS SH SERİSİ R410A SCROLL KOMPRESÖRLER

MODEL	Kod No	DİSP. CC	NOMİNAL GÜÇ	VOLTAJ	EMME BASMA		Btu. 50 Hz.	ÇALIŞMA REJİMİ	YAĞ MİKTARI
SH090 A4ALC	120H0003	88,4	8,0 Hp	380 V / 400V 50HZ 460V 60HZ	11/8"	7/8"	75.000	+15°C / -20 °C (MBP)	3 LT
SH105 A4ALC	120H0211	103,5	9,0 Hp		13/8"	7/8"	87.500		3,3 LT
SH120 A4ALC	120H0013	116,9	10 Hp		13/8"	7/8"	100.000		3,3 LT
SH140 A4ALC	120H0201	132,9	12 Hp		13/8"	7/8"	116.600		3,3 LT
SH161 A4ALC	120H0023	151,7	13 Hp		13/8"	7/8"	134.100		3,3 LT
SH180 B4ABE	120H0275	170,2	15 Hp		15/8"	11/8"	150.000		6,7 LT
SH184 A4ALC	120H0361	170,3	15 Hp		15/8"	11/8"	151.900		6,7 LT
SH240 A4ABE	120H0299	227,6	20 Hp		15/8"	11/8"	200.000		6,7 LT
SH295 A4ABE	120H0827	276,5	25 Hp		15/8"	11/8"	249.800		6,7 LT
SH300 B4ABE	120H0239	285,5	25 Hp		15/8"	11/8"	250.000		6,7 LT
SH380 A4ABE	120H0255	345,0	30 Hp		15/8"	11/8"	316.600		6,7 LT
SH485 A4ABA	120H1064	442,6	40 Hp		15/8"	1 3/8"	404.100		6,7 LT

* Kompresörler kaynak bağlantılıdır. Karter ısıtıcısı 15,2 €'dur

Model	Voltaj	Kondansasyon									
		Evaporasyon	-25 °C	-20 °C	-15 °C	-10 °C	-5 °C	0 °C	+5 °C	+10 °C	+15 °C
SH 090	380 V / 400 V 50 HZ 460V 60 HZ	40 °C	6.497	8.319	10.450	12.930	15.800	19.120	22.930	27.270	32.200
		50 °C	-	-	8.865	11.040	13.560	16.480	19.830	23.670	28.040
SH 105	380 V / 400 V 50 HZ 460V 60 HZ	40 °C	7.613	9.791	12.330	15.300	18.740	22.720	27.300	32.540	38.490
		50 °C	-	-	10.810	13.430	16.430	19.880	23.830	28.350	33.490
SH 120	380 V / 400 V 50 HZ 460V 60 HZ	40 °C	8.720	11.180	14.040	17.370	21.240	25.690	30.810	36.640	43.250
		50 °C	-	-	11.910	14.840	18.230	22.150	26.650	31.800	37.650
SH 140	380 V / 400 V 50 HZ 460V 60 HZ	40 °C	10.690	13.440	16.640	20.380	24.710	29.690	35.410	41.910	49.280
		50 °C	-	-	14.190	17.490	21.320	25.750	30.850	36.670	43.290
SH 161	380 V / 400 V 50 HZ 460V 60 HZ	40 °C	11.670	14.830	18.510	22.790	27.740	33.450	39.990	47.440	55.880
		50 °C	-	-	15.660	19.430	23.790	28.820	34.610	41.230	48.760
SH 180	380 V / 400 V 50 HZ 460V 60 HZ	40 °C	12.720	16.360	20.620	25.590	31.340	37.970	45.560	54.190	63.940
		50 °C	-	-	17.410	21.820	26.930	32.810	39.560	47.250	55.980
SH 240	380 V / 400 V 50 HZ 460V 60 HZ	40 °C	17.870	22.890	28.640	35.240	42.810	51.460	61.320	72.490	85.100
		50 °C	-	-	24.310	30.150	36.830	44.470	53.190	63.090	74.310
SH 300	380 V / 400 V 50 HZ 460V 60 HZ	40 °C	23.150	29.210	36.260	44.440	53.910	64.810	77.280	91.490	107.600
		50 °C	-	-	30.860	38.020	46.320	55.910	66.940	79.540	93.890
SH 380	380 V / 400 V 50 HZ 460V 60 HZ	40 °C	27.500	34.750	43.180	52.990	64.360	77.480	92.550	109.700	129.300
		50 °C	-	-	36.780	45.400	55.420	67.020	80.390	95.730	113.200
SH 485	380 V / 400 V 50 HZ 460V 60 HZ	40 °C	36.230	45.430	56.140	68.590	83.040	99.740	118.900	140.900	165.800
		50 °C	-	-	48.310	59.250	71.920	86.570	103.400	122.800	144.800